

The rugged production LED light that mimics sunlight!

With its purely accurate color temperature and high CRI,
VLite produces a full spectrum quality of soft light at an affordable price.

075MK / 150MK



manufacturers



Postium Korea Co., Ltd.
www.postium.com

VLite-150MK

VLite-075MK



Photometric information of VLite

Division	VLite-150MK		VLite-075MK	
	3200K	5600K	3200K	5600K
Size	542 X 342 X 92.3 mm (21.3 X 13.4 X 3.6 in)		396 X 276.4 X 92.3 mm (15.5 X 10.8 X 3.6 in)	
Weight	6 Kg (13.2 lb)		5.2 Kg (11.4 lb)	
CRI	>97Ra	>95Ra	>97Ra	>95Ra
Color Temperature	3200K ~ 5600K		3200K ~ 5600K	
CCT	3200K	5600K	3200K	5600K
Power Consumption	150W(tungsten 2KW)		75W(tungsten 1KW)	
E. Characteristics	AC 100~240V / 50~60HZ DC 12~24V		AC 100~240V / 50~60HZ DC 12~24V	
Dimming	Manual / DMX 512		Manual / DMX 512	
Color Control	Manual / DMX 512		Manual / DMX 512	
Operating Temp	0 °c ~ 45°c		0 °c ~ 45°c	
Option	V-mount / G-mount			

Lux

	3200K			5600K		
	1M	2M	3M	1M	2M	3M
VLite-150MK	4000 Lux	1000 Lux	400 Lux	4400 Lux	1100 Lux	400 Lux
VLite-075MK	2100 Lux	500 Lux	200 Lux	2400 Lux	600 Lux	200 Lux

- Digital LCD display
- Strong metal construction designed to withstand professional handling.
- A Significant amount of usable light projected over greater distances.
- Professional light at a reasonable price.
- Long life LEDs that last over 30,000 hours (average of 50,000 hours)
- Adjustable Color Temperature from tungsten to daylight and anything in between
- Compatible with Anton Bauer and V-Mount Battery
- Patented technology of radiating heat with no fan and no noise, Absolute silence.
- Smooth and stable control of dimming and color temperature.
- Natural-looking light.
- Standard DMX 512, 5pin XLR in/out
- Accurate and balanced color of light
- Softly diffused light and less glare

VLite-pro

If you are looking for the best light for HD camcorder and DSLR, the answer is VLite Pro.



- Continuous Lighting for HD camcorder & DSLR
- High CRI 97 Ra at 3200K
- Accurate Color temperature and minimal green cast
- Max 560 Lux at 3 ft. with 65° lens
- Adjustable Color Temperature (3200K~5600K)
- Stable Dimming (0% ~ 100%)
- Excellent Uniformity
- No Fan, Flicker free
- 6 ~ 20V DC
- Use Canon LP-E6 battery *not included
- D-Tap support (Anton bauer or V-mount battery)
- Compatible With Canon LP-E6
- Weight : 7 ounce (200g) *not including accessories

Size : 130 X 93 X 33mm (5.11 X 3.66 X 1.29 in)
Weight : 200g (0.440 lbs)